

-25°C Freezer (Separate Refrigerator)



265L



368L

Technical Parameters

Model	BDF-25V265	BDF-25V368
External Size(W*D*H) mm	576*641*1687	720*830*1870
Capacity	Upper:160L Lower:105L	Upper:189L Lower:179L
Temp.Range	Upper: 2°C~8°C Lower: -10°C~-25°C	Upper: 2°C~8°C Lower: -10°C~-25°C
Temp. Accuracy	0.1°C	
Control System	Microprocessor control	
Alarm	Sensor failure alarm, high or low temperature alarm, open the door alarm; Thermostat failure (for BDF-25V368)	
Cooling Method	Upper: Air refrigeration; Lower: Direct cooling	
Refrigerant	CFC free	
Condenser	Wire tube condenser	
Construction	Structure	Unibody design and thickened environmental protection foam insulation layer
	Internal Material	PS plate
	External Material	Pre-coated galvanized plate
Shelf / Drawer / Basket	Upper: 3 shelves, Lower: 4 drawers	Upper:3 plastic dipping shelves Lower:2 plastic dipping shelves, 6 PS drawers
Consumption	125W	300W
Power Supply	AC220V±10%, 50/60Hz	AC220V±10%, 50/60Hz; AC110V ±10%, 60Hz
Package Size(W*D*H) mm	656*696*1739	775*920*1990
Gross Weight	65kg	166kg

-40°C Freezer



58L



90L



368L

Technical Parameters

Model	BDF-40V58	BDF-40V90	BDF-40V368
External Size(W*D*H)	540*620*1115mm	600*610*945mm	720*830*1870mm
Internal Size(W*D*H)	361*405*406mm	440*447*640mm	Upper:580*626*625mm Down:466*636*625mm
Capacity	58L	90L	Upper:189; Down:179L
Type	Vertical		
Temp. Range	-15°C~-40°C		Upper:2°C~8°C Down:-20°C~-40°C
Temp. Accuracy	0.1°C		
Control System	Microprocessor Control LED Display		
Alarm	BDF-40V58: High or low temperature alarm, sensor failure alarm; BDF-40V90&BDF-40V368: High or low temperature alarm, sensor failure alarm, power failure alarm, door open alarm.		
Refrigeration Type	Direct Refrigeration		
Refrigerant	R404a and R23	R290	R600a and R290
Compressor	Unicompressor, imported famous brand compressor		
Material	Structure	Unibody design	
	Internal	304 stainless steel	
	External	Sprayed steel plate	
Shelf	1 pc shelf	2 pcs shelves	Upper:3 pcs shelves Down:2 pcs shelves and 6 drawers
Consumption	340W	252W	402W
Power Supply	AC220V±10%, 50/60Hz; AC110V±10%, 60Hz(except BDF-40V90)		
Package Size	610*690*1275mm	725*735*1160mm	775*920*1990
Gross Weight	98kg	83kg	166kg